

Specifications

* Specifications may be changed without prior notice.
* The capacity may differ slightly, depending on the water and fuel gas quality.

Specifications & Performance

Tankless Gas Water Heater			
Product name	ODW-99B	ODW-120B	ODW-180C
Model		Indoor Wall Mount	ODW-195C
Install Type		Direct Vent / Sealed Combustion	
Flue Type			
Dimension (WxDxH, inch)	15.34" x 8" x 25.17"	18.12" x 8.21" x 26.58"	
Weight(lbs)	51		64
Ignition	Direct Ignition		
Gas Inlet	3/8"		
Connection Sizes	Water Inlet	3/4"	3/4"
	Hot Water Outlet	3/4"	3/4"
Gas Outlets	NG: Max. 99,000 Btu/h	NG: 120,000 Btu/h	NG: 180,000 Btu/h
	LP: Min. 18,000 Btu/h	LP: 20,000 Btu/h	LP: 30,000 Btu/h
Energy Factor	0.91	0.92	0.92
Operating Pressure	15 - 150 PSI		
Minimum Flow Rate	0.52 GPM		
Power/Voltage/Frequency	120V / 60Hz		
Power Consumption(W)	55	60	75
Materials	Casing	Zincized Steel Plate	
	Flue Collar	PPV Polypropylene	
	Heat Exchanger	Spiral Heat Exchanger, Copper Braiding, Copper Tubing, Laminated Heat Exchanger, Aluminum Fin, Copper Tubes	
Accessories	Remote Controller, Anchoring Sensors, Flame Rod, Pressure Relief Valve, Overheat Prevention Device, Flushing Prevention Device, Fan Protection Device		
Safety Devices			
Tube Diameter(inch)	3"	3" or 4"	3" or 4"
Flow Rate(GPM)	4.0	4.8	7.2
Water Flow(GPM)	2.4	2.9	4.2
Fire Settings	96°F - 120°F, 130°F, 140°F, 150°F, 160°F		

Isometric View

ODW-099B - 120B Model

